



WESTINGHOUSE LIGHTING SOLUTIONS

an affiliate of Westinghouse Lighting Corporation,
a Westinghouse Electric Corporation Licensee

QTY.	TYPE	MODEL #

VE SERIES Enclosed & Gasketed / Wide WET LOCATION/ VAPOR TIGHT



END VIEW



Depth 5.95"

4 Lamp across, 14.61" wide
6 Lamp across, 14.61" wide

SIDE VIEW
Length 51.91"

SPECIFICATIONS

Housing / Enclosure –
Engineered Resin, 5VA Flam. rating
UL94(f1)UL746, IP67 Cert / NEMA 4X / NSF rated
Reflector – Anodized, specular aluminum wide beam
Lamp – T5 HO 54 watt linear fluorescent, CRI85
Ballast – 90°C rated, electronic programmed rapid start
Mounting – Stainless Steel V, rated UL 4x weight
Knockouts – (1) each end, Entry hole 1/2" NPT / M20 fittings
Latches (12) – Stainless Steel / captive deluxe design
Diffuser – U.V. stabilized 100% acrylic clear,
frost & prism, or polycarbonate upgrade

FEATURES

- Wet location, vapor tight, wash down design
- Complete containment of lighting equipment
- Withstands moderate impacts
- Widest beam design for enclosed high bay
- Internal geartray access from either side
- Flexible mounting options
- T5, or T8 configurations available
- Popular options: cable / toggle hanging kit, sensor ready, polycarbonate lens

For more specific LTL Test Reports contact us at
info@westinghouse-ls.com

ORDERING INFORMATION

